

Name _____

Date _____

1-1/2" PRECONNECT W/SCBA

COMPETENCY NUMBER:

INDIVIDUAL PERFORMANCE STANDARD:

OBJECTIVE: Firefighter will properly stretch 1½" pre-connect crosslay to a designated area in a smooth and efficient manner while wearing full protective equipment with SCBA (mask to be placed on at entry door). Time starts when order is given and ends when firefighter shows water from nozzle.

TIME STANDARD: 3.0 Minutes

Critical Failures are in BOLD

PROCEDURE		YES	NO
1.	Repeat order, "1-1/2" PRECONNECT".		
2.	Don SCBA pack (mask not worn).		
3.	Face crosslay compartment, grasp nozzle or pull rope, and pull shoulder load partially out of crosslay bed. Rotate under hose load (so as to face away from hose bed) and place hose load on your RIGHT shoulder.		
4.	Position shoulder load so nozzle is in front of shoulder. Remove pull rope near apparatus and let drop to the ground.		
5.	Hold load with RIGHT hand and step out and away from apparatus, allowing hose to clear hose bed.		
6.	Step back toward apparatus making a 1/4 turn to the LEFT and grasp the drag load with LEFT hand.		
7.	Pull remaining hose from the crosslay bed as you walk away. (BE SURE ALL HOSE CLEARS BED AND IS TAUT).		
8.	Advance shoulder and drag load toward designated site. Drop each drag load hose fold as it becomes taut.		
9.	Flake off folds of the shoulder load with RIGHT hand as they become taut. (THROW FOLDS HIGH AND TO THE RIGHT as you advance).		
10.	If IDLH, don SCBA mask. (If car fire approach from a 45° angle)		
11.	Adjust nozzle, bleed off air and flow water appropriately.		
11.	Maintain complete control of charged hoseline.		

Time: _____

Pass Fail

COMMENTS:

EVALUATOR SIGNATURE: _____