

Name _____

Date _____

2 1/2" PRECONNECT (ONE PERSON)

COMPETENCY NUMBER:

INDIVIDUAL PERFORMANCE STANDARD:

OBJECTIVE: Firefighter will properly stretch pre-connected 2-1/2" hoseline to a designated location, form a Keenan's hose loop and show water using all safety precautions while wearing full personal protective equipment and SCBA, without mask. Evolution may be for exposure protection or fire attack.

TIME STANDARD: 1.5 minutes without SCBA mask

Critical Failures are in BOLD

PROCEDURE		YES	NO
1.	Repeat order, "2-1/2 PRECONNECT, EXPOSURE PROTECTION OR FIRE ATTACK".		
2.	Move to 2 1/2" pre-connect bed and pull shoulder load 1/3 out of the bed and rotate under (facing away from hose bed) hose placing shoulder load on RIGHT shoulder. (Remove pull rope).		
3.	Hold load with RIGHT hand and step away from apparatus, allowing hose to clear bed.		
4.	Step back toward apparatus making a 1/4 turn to the LEFT. Grasp two drag loops with the index and middle fingers of LEFT hand (palm down).		
5.	Pull remaining hose from the bed as you walk away. (BE SURE ALL HOSE CLEARS BED AND IS TAUT).		
6.	Advance shoulder load toward designated area. Drop each drag loop one at a time, as it becomes taut.		
7.	Flake off bites of hose from the top of the shoulder load with RIGHT hand, as they become taut. (THROW FOLDS HIGH AND TO THE RIGHT as you advance.)		
8.	Signal for water. (Rotate right hand over head and yell "WATER".)		
9.	Form a Keenan's hose loop and secure with webbing by forming a locking girth hitch.		
10.	If ordered for exposure protection, use fog nozzle. If ordered for fire attack, use 1-1/8" solid bore tip.		
11.	Adjust nozzle, bleed off air and flow water appropriately.		
12.	Maintain complete control of charged hoseline.		

Time: _____

Pass Fail

CRITICAL FAILURE:

- Failure to pull hose correctly (no spaghetti).
- Failure to secure Keenan's loop.
- Failure to be on SCBA when entering IDLH.

COMMENTS:

EVALUATOR SIGNATURE: _____